

Revision Date: 04/15/2019

# SAFETY DATA SHEET

# 1. Identification

Product identifier: GEL VANDAL MARK REMOVER

Other means of identification

**SDS number:** RE1000010423

Recommended restrictions
Product Use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

# Manufacturer

Company Name: Sprayway, Inc.

Address: 1000 INTEGRAM DR

Pacific,MO 63069

Telephone:

630-628-3000

Fax:

Emergency telephone number: 1-866-836-8855

# 2. Hazard(s) identification

# **Hazard Classification**

#### **Physical Hazards**

Flammable aerosol Category 1

**Health Hazards** 

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Aspiration Hazard Category 1

#### **Environmental Hazards**

Acute hazards to the aquatic Category 3 environment

#### **Label Elements**

# **Hazard Symbol:**





Revision Date: 04/15/2019

Signal Word: Danger

**Hazard Statement:** Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of

water/... If skin irritation occurs: Get medical advice/attention. IF

SWALLOWED: Immediately call a POISON CENTER/doctor/... Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50 oC/122oF. Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

#### 3. Composition/information on ingredients



Revision Date: 04/15/2019

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	10 - <25%
2-Propanone	67-64-1	5 - <10%
Propane	74-98-6	5 - <10%
Butane	106-97-8	5 - <10%
Ethanol, 2-butoxy-	111-76-2	1 - <5%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - <5%
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with bentonite	71011-25-1	1 - <5%
Sodium hydroxide (Na(OH))	1310-73-2	0.1 - <1%
Morpholine	110-91-8	0.1 - <1%
Quartz (SiO2)	14808-60-7	0 - <0.1%
Ethanol, 2-methoxy-	109-86-4	0 - <0.1%
1,2-Ethanediamine	107-15-3	0 - <0.1%
Morpholine, 4-ethyl-	100-74-3	0 - <0.1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

**Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

**Inhalation:** Move to fresh air.

**Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** No data available.

# 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.



Revision Date: 04/15/2019

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

up:

**Notification Procedures:** 

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate

Absorb spill with vermiculite or other inert material, then place in a container

area). Stop leak if you can do so without risk.

**Environmental Precautions:** 

Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer.

# 7. Handling and storage

Precautions for safe handling:

Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 2



Revision Date: 04/15/2019

# 8. Exposure controls/personal protection

# **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Lir	mit Values	Source
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	10 ppm	37 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	560 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	Ceiling	500 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	ST ESL		4,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	150 ppm	580 mg/m3	US. Tennessee. OELs. Occupational Exposur Limits, Table Z1A (06 2008)
	ST ESL		1,200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm	375 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		320 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL		1,780 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	3,000 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA PEL	500 ppm	1,200 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		7,800 µg/m3	US. Texas. Effects Screening Levels (Texas



Revision Date: 04/15/2019

				Commission on Environmental Quality) (11
	AN ESL		4,800 µg/m3	2016) US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11 2016)
	TWA	750 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		3,300 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	2,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm	1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm	1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-butoxy-	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm	120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm	120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11



Revision Date: 04/15/2019

Ethanal O (O hostanasha)	TIAVA	40		2016)
Ethanol, 2-(2-butoxyethoxy) Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2013)
Ethanol, 2-(2-butoxyethoxy)-	ST ESL		670 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		67 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling		2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time		2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL		2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	Ceiling		2 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)  US. California Code of Regulations, Title 8,
	Ceiling		2 mg/m3	Section 5155. Airborne Contaminants (09 2006)
Sodium hydroxide (Na(OH)) - Particulate.	AN ESL		2 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		20 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Morpholine	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	30 ppm	105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	20 ppm	70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	20 ppm	70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm	70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm	70 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	30 ppm	105 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA PEL	20 ppm	70 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	30 ppm	105 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		36 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		11 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		40 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Quartz (SiO2) - Respirable fraction.	TWA		0.025 mg/m3	US. ÁCGIH Threshold Limit Values (2008)
Quartz (SiO2) - Respirable dust.	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)



Revision Date: 04/15/2019

Quartz (SiO2) - Respirable dust.	TWA		0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
dust.	OSHA_AC		0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Quartz (SiO2) - Respirable	T PEL		0.05 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.	TWA		0.1 mg/m3	Contaminants (29 CFR 1910.1000) (03 2016)  US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		0.1 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Quartz (SiO2) - Respirable.	TWA		2.4 millions of particles per cubic foot	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		of air 0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
Quartz (SiO2) - Respirable dust.	TWA PEL		0.05 mg/m3	(2000) US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (10
Quartz (SiO2) - Particulate.	ST ESL		14 µg/m3	2016) US. Texas. Effects Screening Levels (Texas
Quartz (SIO2) - Particulate.	31 ESL		14 μg/1113	Commission on Environmental Quality) (11 2016)
	AN ESL		0.27 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-methoxy-	TWA	0.1 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm	0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm	80 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	25 ppm	80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	5 ppm	16 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		16 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	PEL	25 ppm	80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		5 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		160 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
1,2-Ethanediamine	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	10 ppm	25 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	PEL	10 ppm	25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		25 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	ST ESL		250 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)



Revision Date: 04/15/2019

	TWA	10 ppm	25 mg/m3	US. Tennessee. OELs. Occupational Exposure
	TWA	то ррпп	23 mg/m3	Limits, Table Z1A (06 2008)
Morpholine, 4-ethyl-	REL	5 ppm	23 mg/m3	US. NIOSH: Pocket Guide to Chemical
			_	Hazards (2005)
	TWA	5 ppm	23 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
				(1989)
	TWA	5 ppm	23 mg/m3	US. Tennessee. OELs. Occupational Exposure
				Limits, Table Z1A (06 2008)
	TWA PEL	5 ppm	23 mg/m3	US. California Code of Regulations, Title 8,
				Section 5155. Airborne Contaminants (09
				2006)
	PEL	20 ppm	94 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		24 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
				2016)
	TWA	5 ppm		US. ACGIH Threshold Limit Values (2008)
	AN ESL		5.1 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
				2016)
	ST ESL		51 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
				2016)
	ST ESL		240 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
				2016)

**Biological Limit Values** 

Chemical Identity	<b>Exposure Limit Values</b>	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2- Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

# Appropriate Engineering Controls

No data available.

# Individual protection measures, such as personal protective equipment

**General information:** Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels

to an acceptable level.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).



Revision Date: 04/15/2019

**Skin Protection** 

**Hand Protection:** No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Avoid contact with eyes. Observe good industrial hygiene practices. When Hygiene measures:

> using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands

before breaks and immediately after handling the product.

# 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: Spray Aerosol Color: No data available. Odor: No data available. **Odor threshold:** No data available. pH: No data available. No data available. Melting point/freezing point: Initial boiling point and boiling range: No data available. Flash Point: -104.44 °C

**Evaporation rate:** No data available. Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available. Flammability limit - lower (%): No data available. Explosive limit - upper (%): No data available. **Explosive limit - lower (%):** No data available.

Vapor pressure: 413.682 - 517.1025 hPa (20 °C)

689.47 - 827.364 hPa (50 °C)

Vapor density: No data available. Density: No data available. Relative density: No data available.

Solubility(ies)

Solubility in water: No data available. Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available.

No data available. Auto-ignition temperature: **Decomposition temperature:** No data available. Viscosity: No data available.



Revision Date: 04/15/2019

# 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

Products:

No data available.

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

# Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

### Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 17,885.53 mg/kg

Dermal

**Product:** ATEmix: 11,258.7 mg/kg

Inhalation

**Product:** ATEmix: 359.28 mg/l

ATEmix: 32.66 mg/l

Repeated dose toxicity

**Product:** No data available.



Revision Date: 04/15/2019

Specified substance(s):

Benzene, methyl-LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target

> Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation

Experimental result, Key study

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result. Kev study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Propane

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Butane

Experimental result. Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Ethanol, 2-butoxy-

Experimental result, Key study

NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key

NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation

Experimental result, Key study

Ethanol, 2-(2-NOAEL (Rat(Female, Male), Oral, 90 d): > 255 mg/kg Oral Experimental butoxyethoxy)-

result, Supporting study

LOAEL (Rat, Oral, 30 d): 94 mg/kg Oral Experimental result, Supporting

study

NOAEL (Rat(Female, Male), Oral, 30 d): 94 mg/kg Oral Experimental result,

Supporting study

NOAEL (Rat, Oral, 30 d): 51 mg/kg Oral Experimental result, Supporting

NOAEL (Rat(Female), Inhalation, 5 Weeks): 6 ppm(m) Inhalation

Experimental result, Supporting study

Morpholine LOAEL (Rat(Female), Oral, 56 d): 500 mg/kg Oral Experimental result, Key

NOAEL (Rat(Female, Male), Inhalation): 36 ppm(m) Inhalation Experimental

result, Key study

NOAEL (Rat(Female, Male), Inhalation): 50 ppm(m) Inhalation Experimental

result, Key study

LOAEL (Rat(Male), Oral, 90 d): 71 mg/kg Oral Experimental result, Key Ethanol, 2-methoxy-

study

NOAEL (Rabbit(Female, Male), Inhalation, 13 Weeks): 100 ppm(m)

Inhalation Experimental result, Key study

LOAEL (Rat(Female), Inhalation, 13 Weeks): 100 ppm(m) Inhalation

Experimental result, Supporting study

1,2-Ethanediamine NOAEL (Rat(Female, Male), Inhalation, 6 Weeks): 59 ppm(m) Inhalation

Experimental result. Key study

LOAEL (Rat(Female, Male), Oral, 3 Months): 114 mg/kg Oral Experimental

result, Key study

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):



Revision Date: 04/15/2019

Benzene, methylin vivo (Rabbit): Irritating Experimental result, Key study

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

in vivo (Rabbit): Irritating Experimental result, Key study Ethanol, 2-butoxy-

Ethanol, 2-(2in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Not irritant Experimental result, Supporting study butoxyethoxy)-

in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Slightly irritating Experimental result, Key study

in vivo (Rat): classification not possible based on data Experimental result,

Supporting study

in vivo (Rabbit): Irritating Experimental result, Supporting study Morpholine

in vivo (Rabbit): Corrosive Experimental result, Supporting study

in vivo (Rabbit): Corrosive Experimental result, Key study

in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study

in vivo (Rabbit): Corrosive Experimental result, Key study

in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study

Ethanol, 2-methoxyin vivo (Rabbit): Not irritant Experimental result, Key study

1,2-Ethanediamine in vivo (Rabbit): Corrosive Experimental result, Key study

Morpholine, 4-ethyl-Assessment (Various): Corrosive Expert judgment

### Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Benzene, methyl-Rabbit, 24 - 72 hrs: Not irritating

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Ethanol, 2-butoxy-Rabbit, 24 - 72 hrs: Irritating

Rabbit, 24 hrs: Moderately irritating Ethanol, 2-(2butoxyethoxy)-Rabbit, 24 - 72 hrs: Highly irritating

Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 48 hrs: Moderately irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 72 hrs: Moderately irritating Rabbit, 48 hrs: Not irritating

Rabbit, 24 hrs: Moderately irritating

Sodium hydroxide

Corrosive (Na(OH))

Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide-

Slightly irritating to eyes



Revision Date: 04/15/2019

1,2-Ethanediamine Rabbit, 24 - 72 hrs: Corrosive

Morpholine, 4-ethyl- Corrosive

Respiratory or Skin Sensitization

**Product:** No data available.

Specified substance(s):

Benzene, methyl2-Propanone
Skin sensitization:, in vivo (Guinea pig): Non sensitising

butoxyethoxy)-

Morpholine Skin sensitization:, in vivo (Guinea pig): Non sensitising Ethanol, 2-methoxy1,2-Ethanediamine Skin sensitization:, in vivo (Guinea pig): Non sensitising May cause sensitization by inhalation and skin contact.

Carcinogenicity

**Product:** No data available.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

#### **US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

#### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specified substance(s):

Benzene, methyl- Suspected of damaging fertility or the unborn child.

Ethanol, 2-methoxy- May cause adverse reproductive effects - such as infertility based on animal

data.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

Specified substance(s):

Benzene, methyl2-Propanone
Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

Specified substance(s):



Revision Date: 04/15/2019

Benzene, methyl- Category 2

**Aspiration Hazard** 

**Product:** No data available.

Specified substance(s):

Benzene, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

#### 12. Ecological information

#### **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key

study

Ethanol, 2-(2- LC 50 (Goldfish (Carassius auratus), 24 h): 2,700 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 96 h): 1,300 mg/l Mortality

LC 50 (Bluegill (Lepomis macrochirus), 96 h): 1,300 mg/l Mortality LC 50 (Inland silverside (Menidia beryllina), 96 h): 2,000 mg/l Mortality LC 50 (Carp (Leuciscus idus melanotus), 48 h): 1,805 mg/l Mortality

LC 50 (Carp (Leuciscus idus melanotus), 48 h): 2,304 mg/l Mortality

Sodium hydroxide

(Na(OH))

LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality

LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting

study

Morpholine LC 50 (Oncorhynchus mykiss, 96 h): 180 mg/l Experimental result, Key

study

LC 0 (Vala mugil engeli, 96 h): 100 mg/l Experimental result, Key study LC 50 (Vala mugil engeli, 96 h): 179 mg/l Experimental result, Key study LC 50 (Oncorhynchus mykiss, 96 h): 380 mg/l Experimental result, Key

study

LC 100 (Vala mugil engeli, 96 h): 320 mg/l Experimental result, Key study

Ethanol, 2-methoxy- LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 14,000

- 18,000 mg/l Mortality



Revision Date: 04/15/2019

1,2-Ethanediamine LC 50 (Poecilia reticulata, 96 h): 640 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality

LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Ethanol, 2-butoxy- EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

Ethanol, 2-(2- LC 50 (Water flea (Daphnia magna), 24 h): 2,850 mg/l Mortality

butoxyethoxy)- ED 0 (Daphnia magna, 48 h): 1,870 mg/l Experimental result, Supporting

study

LC 100 (Daphnia magna, 24 h): 3,850 mg/l Experimental result, Supporting

study

EC 50 (Daphnia magna, 24 h): 3,200 mg/l Experimental result, Supporting

study

ED 0 (Daphnia magna, 24 h): 2,333 mg/l Experimental result, Supporting

study

Sodium hydroxide

(Na(OH))

EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l

Intoxication

Morpholine EC 100 (Daphnia magna, 24 h): 260 mg/l Experimental result, Supporting

study

EC 50 (Daphnia magna, 24 h): 101 mg/l Experimental result, Supporting

study

ED 0 (Daphnia magna, 24 h): 68 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 48 h): 45 mg/l Experimental result, Key study EC 50 (Water flea (Daphnia magna), 24 h): 112 - 127 mg/l Intoxication

Ethanol, 2-methoxy- EC 50 (Daphnia magna, 48 h): 27,000 mg/l Experimental result, Key study

1,2-Ethanediamine EC 50 (Daphnia magna, 48 h): 16.7 mg/l Experimental result, Key study

#### Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study

LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

1,2-Ethanediamine NOAEL (Gasterosteus aculeatus): > 10 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):



Revision Date: 04/15/2019

Benzene, methyl- LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study

NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Ethanol, 2-butoxy- EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study

Morpholine NOAEL (Daphnia magna): 5 mg/l Experimental result, Key study

EC 50 (Daphnia magna): 12 mg/l Experimental result, Key study

Ethanol, 2-methoxy- NOAEL (Daphnia magna): > 500 mg/l Experimental result, Key study

1,2-Ethanediamine NOAEL (Daphnia magna): 0.16 mg/l Experimental result, Key study

**Toxicity to Aquatic Plants** 

**Product:** No data available.

# Persistence and Degradability

Biodegradation

**Product:** No data available.

Specified substance(s):

Benzene, methyl- 100 % (14 d) Detected in water. Experimental result, Weight of Evidence

study

86 % Detected in water. Experimental result, Weight of Evidence study

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result. Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Ethanol, 2-butoxy- 90.4 % Detected in water. Experimental result, Key study

Ethanol, 2-(2- 14 % Detected in water. Experimental result, Supporting study butoxyethoxy)- 60.8 % Detected in water. Experimental result, Supporting study

2 % Detected in water. Experimental result, Supporting study 49.2 % Detected in water. Experimental result, Supporting study 13.1 % Detected in water. Experimental result, Supporting study

10.1 70 Detected in Water. Experimental result, Supporting study

80 - 94 % (24 h) Sediment Experimental result, Key study 5.5 % Detected in water. Experimental result, Key study 98 % Detected in water. Experimental result, Supporting study

2 % Detected in water. Experimental result, Key study17 % Detected in water. Experimental result, Supporting study

Ethanol, 2-methoxy- 82 % (14 d) Detected in water. Experimental result, Supporting study

74 % Detected in water. Experimental result, Key study

1,2-Ethanediamine 88 % Detected in water. Experimental result, Key study

**BOD/COD Ratio** 

Morpholine



Revision Date: 04/15/2019

**Product:** No data available.

Bioaccumulative potential

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

Benzene, methyl- Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment

Experimental result, Key study

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Morpholine Cyprinus carpio, Bioconcentration Factor (BCF): <= 0.65 Aquatic sediment

Experimental result, Key study

Cyprinus carpio, Bioconcentration Factor (BCF): < 2.8 Aquatic sediment

Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

**Mobility in soil:** No data available.

Known or predicted distribution to environmental compartments

Benzene, methyl2-Propanone
Propane
Butane
Ethanol, 2-butoxyEthanol, 2-(2No data available.
No data available.

butoxyethoxy)-

Quaternary ammonium No data available.

compounds.

benzyl(hydrogenated tallow

alkyl)dimethyl,

bis(hydrogenated tallow alkyl)dimethylammonium

salt with bentonite

Sodium hydroxide (Na(OH))

Morpholine

Quartz (SiO2)

Ethanol, 2-methoxy1,2-Ethanediamine

Morpholine, 4-ethyl
No data available.

Other adverse effects: Harmful to aquatic organisms.

#### 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.



Revision Date: 04/15/2019

# 14. Transport information

#### DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

**IMDG** 

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): – EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

# 15. Regulatory information

**US Federal Regulations** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)



Revision Date: 04/15/2019

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> Quartz (SiO2)

OSHA hazard(s) kidney effects

lung effects

immune system effects

Cancer

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Benzene, methyl-	lbs. 1000
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Sodium hydroxide	lbs. 1000
(Na(OH))	
Morpholine	lbs. 100
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable aerosol Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Toxic to reproduction Aspiration Hazard

# SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
2-Propanone	<del></del>	
1,2-Ethanediamine	lbs. 5000	lbs. 10000

#### SARA 304 Emergency Release Notification

SANA 304 Linergency Nelease Notification					
Chemical Identity	Reportable quantity				
Benzene, methyl-	lbs. 1000				
2-Propanone	lbs. 5000				
Propane	lbs. 100				
Butane	lbs. 100				
Ethanol, 2-butoxy-					
Ethanol, 2-(2-					
butoxyethoxy)-					
Sodium hydroxide	lbs. 1000				
(Na(OH))					
Morpholine	lbs. 100				
Ethanol, 2-methoxy-					
1,2-Ethanediamine	lbs. 5000				
Morpholine, 4-ethyl-	lbs. 100				



Revision Date: 04/15/2019

#### SARA 311/312 Hazardous Chemical

Chemical IdentityThreshold Planning Quantity1,2-EthanediaminelbsBenzene, methyl-10000 lbs2-Propane10000 lbsPropane10000 lbs

Butane 10000 lbs
Ethanol, 2-butoxy- 10000 lbs
Ethanol, 2-(2- 10000 lbs

butoxyethoxy)-

Quaternary ammonium 10000 lbs

compounds,

benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium

salt with bentonite

Sodium hydroxide 10000 lbs

(Na(OH))

Morpholine 10000 lbs Quartz (SiO2) 10000 lbs Ethanol, 2-methoxy- 10000 lbs Morpholine, 4-ethyl- 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for manufacturing and

Chemical Identity other users processing

Benzene, methyl- lbs lbs.
Ethanol, 2-butoxy- N230 lbs N230 lbs.
Ethanol, 2-(2- N230 lbs N230 lbs.

butoxyethoxy)-

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

#### **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methylQuartz (SiO2)

Carcinogenic. 05 2011

Sthand, 2 methody.

Developmental toxin, 03 2008

Ethanol, 2-methoxyEthanol, 2-methoxyDevelopmental toxin. 03 2008
Male reproductive toxin. 03 2008

# **US. New Jersey Worker and Community Right-to-Know Act**

#### **Chemical Identity**

Benzene, methyl-2-Propanone Propane Butane

Ethanol, 2-butoxy-

Ethanol, 2-(2-butoxyethoxy)-



Revision Date: 04/15/2019

# **US. Massachusetts RTK - Substance List**

# **Chemical Identity**

Quartz (SiO2) 1,2-Ethanediamine

# US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Benzene, methyl-2-Propanone Propane Butane Ethanol, 2-butoxy-Ethanol, 2-(2-butoxyethoxy)-9-Octadecenoic acid (9Z)-

#### **US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

# International regulations

#### Montreal protocol

Not applicable

# Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable



Revision Date: 04/15/2019

**Inventory Status:** 

Australia AICS: On or in compliance with the inventory

Canada DSL Inventory List: On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: On or in compliance with the inventory

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

US TSCA Inventory:

On or in compliance with the inventory

New Zealand Inventory of Chemicals:

On or in compliance with the inventory

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: On or in compliance with the inventory

Taiwan Chemical Substance Inventory:

On or in compliance with the inventory

# 16.Other information, including date of preparation or last revision

**Issue Date:** 04/15/2019

**Revision Information:** No data available.

Version #: 1.0

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.